Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

SCENICVIEW A24W-3A

Value Line Wide TFT display – Enter the world of LCD displays

Issue November 2007

Pages 2

Enjoy the spacious viewing area of the 24 inch wide format display in modern office applications or document management with two pages sied by side.

Excellent visual ergonomics for the office

- 16:10 wide format
- 1920 x 1200 maximum resolution
- 1000:1 typical Contrast
- 400 cd/m²
- 170° typical viewing angle

Height adjustable stand

- Height adjustment
- Tilt
- Swivel

Flexible connectivity

- Analog D-SUB
- Digital DVI-D
- D-SUB and DVI-D cables included

Representative Design

- Elegant, slender body
- Ergonomic light grey housing color
- Integrated speakers
- Integrated power supply

Exceptionally Eco-friendly

- TCO`03
- Energy Star
- RoHS
- WEEE

ENERGY STAR

TCO Development TCO'03 DISPLAYS www.tcodevelopment.com

Works with Windows Vista™

Visible screen diagonal	24 inch (61 cm)	
Graphics display (dependent on graphics processor)		
Pixels	1920 x 1200	
Pixels *)	1680 x 1050	
Pixels *)	1280 x 1024	
Pixels *)	1280 x 800	
Pixels *)	1024 x 768	
Pixels *)	800 x 600	
Pixels *)	640 x 480	
*) interpolated		
Text display (dependent on graphics processor)		
Pixels (max. 75 Hz)	720 x 400	
Picture size	518 x 324 mm	
Pixel pitch	0.270 mm	
Frequencies		
Horizontal	30 - 82 kHz	
Vertical	55 - 75 Hz	
Brightness typical	400 cd/m^2	
Contrast typical	1000:1	
Viewing angle typical	CR>5:1	CR>10:1
Horizontal	170°	160°
Vertical	170°	160°
Response time typical	5 ms	
Plug & Play	VESA DDC CI	
Ease-of-use menu		
Direct key access	auto adjust, input, mute	
Brightness / contrast	brightness, contrast, black level, auto level	
Image adjust	H, V position, clock, phase	
Audio	Volume, mute	
Color	sRGB, 6500 K, 9300 K, native, customer settings	
OSD setup	language, position, time out	
Advanced	DDCI, resolution notifier, factory recall, Input select	
Information	Model name, S/N, Resolution/mode, Signal input	
Base features		
Height adjust range	100 mm	
Tilt angle	-5° / + 20°	
Swivel	+/- 45°	
Audio characteristics		
Volume control	digital	
Audio signal input (from PC)	3.5 mm stereo phone jack	
Sound output	1.0 W (L) + 1.0 W (R)	

Electrical values	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw typical	
Operation (w/o sound)	
max. Brightness	90 W
with EPA settings	60 W
Power save mode (Off- mode)	1 W
Soft switch off (front)	< 1 W
Protection class	1
Temperatures / dimensions / weight	
Ambient temperature (to IEC721)	
Recommended range	15°C to 32°C
Limit	5°C to 35°C
Dimensions (lowest position) (H x W x D)	431 x 565 x 212
Dimensions without base (H x W x D)	378 x 565 x 83
Weight unpacked / packed	9 kg
without base unpacked	7 kg
Reliability typical	
MTBF (demonstrated)	70,000 h
Lifetime of LCD (brightness > 50 % of original brightness)	50,000 h
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and suppression	CE certification according RFI to EC Directive 2004/108/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'03
Ecology	RoHS, WEEE, IT-Eco-declaration Energy Star (EPA 4.1)
Video input	1 x D-SUB analog 1 x DVI-D
Data cable (1.8 m) detachable on display	D-SUB (15-pin) analog DVI-D digital Audio cable
Power cable (1.8 m)	for wall socket Euro-Schuko-Type CEE7
Integrated power supply Plug type on display side	IEC-320-C13
Special features	Kensington Lock prepared, standardized mounting interface according VESA FPMPMI (100 mm)
Order code	S26361-K1179-V150

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu-siemens.com/terms_of_use.html

Copyright © Fujitsu Siemens Computers 11/2007

Published by
Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

Company stamp